


Sorting

6 3 9 2 7 1 5 Sorting → 1 2 3 5 6 7 9

- Internal sort: records fit in internal memory (direct access)
External sort: on external devices — (Block transfer)
disk, tape → (Sequential access)
- $T: \geq N \log N$ (Key comparisons)
 - N^2 : selection, insertion, bubble - elementary
 - $N \log N$: quick (average), heap (worst)
 - N : radix sort, distribution counting
- S : in place : NO extra memory
- Stable : 2 4 3 | 2 5 | 2 → 1 1 2 2 2 3 4 5
Unstable : → 1 1 2 2 2 3 4 5

3sort

if $a > b$ then swap(a, b)
if $a > c$ then swap(a, c)
if $b > c$ then swap(b, c)



• Selection sort

S O R T I N G
 G O R T I N S
 G I R T O N S
 G I N T O R S
 G I N O T R S
 G I N O R T S
 G I N O R S T

```

for i := 1 to N-1 do {
    min := i;
    for j := i+1 to N do
        if a[j] < a[min] then
            min := j;
    Swap(a[i], a[min]);
}
    
```

$$T = \frac{N^2}{2} + NM \quad \leftarrow \text{record size}$$

- Good for small N, large M

• Insertion sort

S O R T I N G
O S R T I N G
O R S T I N G
 ⋮
 I O R S T N G
 -∞ I N O R S T G
G I N O R S T

$$T = \frac{N^2}{4} + \frac{N^2}{8} M$$

- For almost sorted file.
- Compare adjacent pairs only $\Downarrow$ longer leap

• Shell sort

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

A S O R T I N G E X A M P L E

$h=13$

A E O R T I N G E X A M P L S

$h=4$

A E A G E I N M P L O R T X S

$h=1$ ← insertion sort

A A E E G I L M N O P R S T X

h -sequence: ..., 1093, 364, 121, 40, 13, 4, 1

• Bubble sort

for $i := N$ downto 1

for $j := 2$ to i do

if $a[j-1] > a[j]$ then

swap($a[j-1]$, $a[j]$)

6	3	3	2	2	1
3	6	2	3	1	2
9	2	6	1	3	3
2	7	1	5	5	5
7	1	5	6	6	6
1	5	7	7	7	7
5	9	9	9	9	9

$$T = \frac{N^2}{2} + \frac{N^2}{2} M$$

Distribution Counting

• Key $\in \{0, 1, \dots, M-1\}$

$M=8$

$i \rightarrow$	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
$a[i] \rightarrow$	3	1	1	0	3	7	5	5	2	4	2	1	0	2	6	<u>4</u>

	0	1	2	3	4	5	6	7
Count[i]	2	3	3	2	2	2	1	1

	0	1	2	3	4	5	6	7
Count[i]	2	5	8	10	<u>12</u>	14	15	16

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
$b[i]$	0	0	1	1	1	2	2	2	3	3	4	<u>4</u>	5	5	6	7

```
for i := N downto 1 do {  
    b[count[a[i]]] := a[i];  
    count[a[i]] := count[a[i]] - 1;  
}
```

• $T = 2N$

• Stable

Quick Sort

Quicksort(l, r)

if $r > l$ then {

$v := a[r]; i := l-1; j := r;$

repeat

repeat $i := i+1$ until $a[i] \geq v;$

repeat $j := j-1$ until $a[j] \leq v;$

$t := a[i]; a[i] := a[j]; a[j] := t;$

until $j \leq i;$

$a[j] := a[i]; a[i] := a[r]; a[r] := t;$

quicksort($l, i-1$);

quicksort($i+1, r$);

}

$i := \text{partition}(l, r);$

← Until $j < i;$

← quicksort(l, j);

$a[r] \leftrightarrow a[i]$

$i := \text{Partition}(l, r)$

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
	A	S	O	R	T	I	N	G	E	X	A	M	P	L	E	sentinel
-∞	A	A									S	M	P	L	E	
	A	A	E						O	X	S	M	P	L	E	
	A	A	E	E	T	I	N	G	O	X	S	M	P	L	R	
	$\leq a[i]$			$\uparrow$ $a[i]$	$\geq a[i]$											

• Inefficiently on sorted file.

• $a[i] \geq v$

$a[j] \leq v$


⇒

(1) Sentinel


(2) balance partition

(3) less complicated


(1)



(2)




(3)



Improvements (25% ~ 30%)

• Removing recursion:



$l := 1; \quad r := N; \quad \text{initStack}; \quad \text{push}(l); \quad \text{push}(r);$

repeat

if $r > l$ then {

$i := \text{partition}(l, r);$

if $i - l > r - i$ then

$\text{push}(l); \text{push}(i-1); \quad l := i+1;$

← put larger subfile on stack

else $\text{push}(i+1); \text{push}(r); \quad r := i-1;$

else

$r := \text{pop}; \quad l := \text{pop};$

until $\text{Stack} = \emptyset$

$\lg N$ entries on stack

• Small subfile

if $r - l \leq 15$ then $\text{insertion}(l, r);$


• Median-of-three

$\text{threeSort}(a[l], a[\frac{l+r}{2}], a[r]);$

$\text{swap}(a[\frac{l+r}{2}], a[r-1]);$

$\text{partition}(l+1, r-2);$

⋮



• No sentinel.

• $\text{partition}(l+1, r-2)$

• $i \approx \frac{l+r}{2}$

Selection : Find Kth Smallest ($K = \frac{N}{2}$, median)

- K small : (selection sort)^K $T = NK$
- K larger : priority queue: (insert)^K (replace)^{N-K} $T = N \log K$
- K Large :

Recursive

Select(l, r, K)

```


if r > l then {
    i := partition(l, r);
    if i > l + K - 1 then
        Select(l, i-1, K);
    if i < l + K - 1 then
        Select(i+1, r, K-i);
}
    
```

Non recursive K: global

Select(K) $l := 1; r := N;$

```

While r > l do {
    i := partition(l, r);
    if i ≥ K then
        r := i-1;
    if i ≤ K then
        l := i+1;
}
    
```



Example:

↓

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
A	S	O	R	T	I	N	G	E	X	A	M	P	L	E
A	A	E	E	T	I	N	G	O	X	S	M	P	L	R
				L	I	N	G	O	P	M	R	X	T	S
				L	I	G	M	O	P	N				
							M							

$$T = N^2$$

Worst

$$N + K \log \frac{N}{K}$$


Average

Radix Sorting (string sorting)

(M進位)

- Keys represented in base-M system ($M = \text{radix}$)
- process + compare pieces of keys vs. Compare + exchange

$$\text{bits}(x, k, j) := (x \text{ div } 2^k) \bmod 2^j$$



$$T = Nb \approx N \log N$$

(1) Radix Exchange sort ($L \rightarrow R$)

$M=2$

A 00001	A 00001	A 00001	A 00001	A 00001	A 00001
<u>S</u> 10011	E 00101	E 00101	A 00001	A 00001	A 00001
O 01111	O 01111	A 00001	E 00101	E 00101	E 00101
R 10010	L 01100	E 00101	E 00101	E 00101	E 00101
T 10100	M 01101	G 00111	<u>G 00111</u>	G 00111	
I 01001	I 01001	I 01001	<u>I 01001</u>		
N 01110	N 01110	N 01110	N 01110	L 01100	L 01100
G 00111	G 00111	M 01101	M 01101	M 01101	M 01101
E 00101	E 00101	L 01100	L 01100	N 01110	N 01110
X 11000	A 00001	<u>O 01111</u>	<u>O 01111</u>	<u>O 01111</u>	O 01111
A 00001	X 11000	S 10011	S 10011	P 10000	
M 01101	T 10100	T 10100	R 10010	R 10010	L 10010
P 10000	P 10000	F 10000	P 10000	S 10011	L 10011
L 01100	R 10010	R 10010	T 10100		
<u>E</u> 00101	S 10011	X 11000			

2) Straight Radix sort ($R \rightarrow L$)

124, 324, 223, 321, 123, 131

$$M = 2^m = 4$$

321, 131, 223, 123, 124, 324

321, 223, 123, 124, 324, 131

123, 124, 131, 223, 321, 324

1 → 321, 131
2 →
3 → 223, 123
4 → 124, 324

1 →
2 → 321, 223, 123, 124, 324
3 → 131
4 →

1 → 123, 124, 131
2 → 223
3 → 321, 324
4 →

- Each pass ensures **stable** uses **distribution counting**

• Example:
 $m=1$

A 00001	R 10010	T 10100	X 11000	P 10000	A 00001
S 10001	T 10100	X 11000	P 10000	A 00001	A 00001
O 01111	N 01110	P 10000	A 00001	A 00001	E 00101
R 10010	X 11000	L 01100	I 01001	R 10010	E 00101
T 10100	P 10000	A 00001	A 00001	S 10011	G 00111
I 01001	L 01100	I 01001	R 10010	T 10100	I 01001
N 01110	A 00001	E 00101	S 10011	E 00101	L 01100
G 00111	S 10011	A 00001	T 10100	E 00101	M 01101
E 00101	O 01111	M 01101	L 01100	G 00111	N 01110
X 11000	I 01001	E 00101	E 00101	X 11000	O 01111
A 00001	G 00111	R 10010	M 01101	I 01001	P 10000
M 01101	E 00101	N 01110	E 00101	L 01100	R 10010
P 10000	A 00001	S 10011	N 01110	M 01101	S 10011
L 01100	M 01101	O 01111	O 01111	N 01110	T 10100
E 00101	E 00101	G 00111	G 00111	O 01111	X 11000

3) Linear sort

(i) 4 passes straight radix sort ($m = \frac{b}{4}$) $\Rightarrow$ Linear

(ii) 2 passes on leading bits (almost sorted now)
+ insertion sort

$$T = 4N$$

Priority Queue

- Example: Job Scheduler, Key = Priority

- Operations:

Construct

$= (\text{insert})^N$

- * Insert

- * Remove largest element

Replace(v) largest with new item v (unless v is larger) $= \text{insert} + \text{remove}$

Change priority of an element $= \text{delete} + \text{insert}$

Join 2 queues

Delete(v)

• Priority queue for Sorting $= (\text{insert})^N (\text{remove})^N$

1) unordered list $\Rightarrow$ Selection Sort : burden on remove


2) ordered list $\Rightarrow$ Insertion Sort : " insert

3) Heap $\Rightarrow$ Heap sort : amortize

$$T = N \log N$$

• Heap


$$a[j] \geq a[2j] \\ \geq a[2j+1]$$




i	1	2	3	4	5	6	7	8	9	10	11	12
a[i]	X	T	O	G	S	M	N	A	E	R	A	I

j div 2


Insert(P)



Replace(C)



Remove



• Remove

remove := a[i];
a[i] := a[N]; N := N-1;
downheap(1);

$$T = O(\log N)$$

• Upheap(k)

• Insert(v)


N := N+1; a[N] := v;
upheap(N);

• Downheap(k)


• Replace(v)

a[0] := v; downheap(0);
replace := a[0];

Top-down :



Bottom-up :



• Heap sort

(1) (insert)^M(remove)^M

• Top down

(2)

$N := M;$

for $k := \frac{M}{2}$ downto 1 do

 downheap(k);


} Construct Heap: : Bottom up

Repeat

 swap(a[1], a[N]); $N := N - 1$

 downheap(1)

Until $N \leq 1$



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
A	S	O	R	T	I	N	G	E	X	A	M	P	L	E
						N							L	E
					P						M	I		
				X					T	A				
			R				G	E						
		P			O	N					M		L	E
	X		R	T			G	E	S	A				
X	T	F	R	S	O	N	G	E	A	A	M	I	L	E
T	S	P	R	E	O	N	G	E	A	A	M	I	L	
S	R	P	L	E	O	N	G	E	A	A	M	I		
R	L	P	I	E	O	N	G	E	A	A				
P	L	O	I	E	M	N	G	E	A	A				
O	L	N	I	E	M	A	G	E	A					
N	L	M	I	E	A	A	G	E						
M	L	E	I	E	A	A	G							
L	I	E	G	E	A	A								
I	G	E	A	E	A									
G	E	E	A	A										
E	A	A												
A	A													
A	A	E	E	G	I	L	M	N	O	P	R	S	T	X

Selection & Merging


- **Selection**: find k th smallest
median ($k = \frac{N}{2}$)
split file (divide + conquer)
- **Merging**: sorted file + sorted file $\leftrightarrow$ larger sorted file
merge file

Quick Sort: divide 2 sorted file $\Rightarrow$ whole file sorted
: most done before recursive calls (conquer & Divide)


Merge Sort: " + merge $\Rightarrow$ "
: most done after recursive calls (Divide & Conquer)

• Merge

2-Way merge:
array merge:



list merge:



$$T = M + N$$

$i := 1; j := 1;$

$a[M+1] := \infty; b[N+1] := \infty;$

for $K := 1$ to $M+N$ do

if $a[i] < b[j]$ then $c[k] := a[i]; i := i+1;$

else $c[k] := b[j]; j := j+1;$

• Merge Sort


• array

$m := (l+r) \div 2;$


$\text{mergeSort}(l, m); \text{mergeSort}(m+1, r);$

$\text{Copy}(a, b, l, m); \text{CopyR}(a, b, m+1, r);$

merge



List



```

a := C; b := C.next; b := b.next; b := b.next;
while b ≠ z do
    C := C.next; b := b.next; b := b.next;
    b := C.next; C.next := z;
mergeSort := Merge(mergeSort(a), mergeSort(b));
    
```

• Build up small sorted file into larger ones (top down)

$$M_N = 2 M_{\frac{N}{2}} + N$$

$$= N \lg N$$

• Example:

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
A	S	O	R	T	I	N	G	E	X	A	M	P	L	E
	O	S												
A	O	S												
			R	T										
					I	N								
			I	N	R	T								
A	I	N	O	R	S	T								
							E	G						
									A	X				
							A	E	G	X				
											M	P		
													E	L
											E	L	M	P
							A	E	E	G	L	M	P	X
A	A	E	E	G	I	L	M	N	O	P	R	S	T	X

Merge Sort (Bottom up)

N=1

2

4

8


16

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
A	S	O	R	T	I	N	G	E	X	A	M	P	L	E
A	S	O	R	I	T	G	N	E	X	A	M	L	P	E
A	O	R	S	G	I	N	T	A	E	M	X	E	L	P
A	G	I	N	O	R	S	T	A	E	E	L	M	P	X
A	A	E	E	G	I	L	M	N	O	P	R	S	T	X

```

begin
  N:=1; new(head); head↑.next:=c;
  repeat
    todo:=head↑.next; c:=head;
    repeat
      t:=todo;
      a:=t; for i:=1 to N-1 do t:=t↑.next;
      b:=t↑.next; t↑.next:=z;
      t:=b; for i:=1 to N-1 do t:=t↑.next;
      todo:=t↑.next; t↑.next:=z;
      c↑.next:=merge(a, b);
      for i:=1 to N+N do c:=c↑.next
    until todo=z;
    N:=N+N;
  until a=head↑.next;
  mergesort:=head↑.next
end;
  
```

$$N+N \rightarrow 2N$$



N=2


N=4

- Stable
- No stack

External Sorting


- External memory: disk, tape, ...
 - Accessing cost dominates
 - System aspect as important as algorithm (technology dep.)
 - 2-level memory hierarchy
-
- General Sort-Merge method:
 - Break file into sorted blocks (runs)
+ Merge into larger block
-
- Goal:
Reduce # passes

Memory Hierarchy



• Balanced P-way merge

(1) Generate Initial Runs :



(2) P-way Merge

tape 4 A A G I N O R S T •

tape 5 D E G G I M N N R •

tape 6 A E E L M P X •

tape 1 A A A D E E E G

- $\log_p \frac{N}{M}$ passes
- 4-tapes are enough
- How to merge ?

• Replacement Selection

Use Priority Queue

• For P-way merge:

tape1: A O S • D M N • ...

tape2: I R T • E G R • ...

tape3: A G N • G I N • ...

tape4: A A G I N O R S T •

• Form Initial Runs

Heap, size P

1	2	3
A	I	A
A	I	<u>O</u>
G	I	O
I	N	O
N	R	O
O	R	• ↔ ∞
R	S	•
S	T	•
T	•	•

Heap. size = M

R	A	S	O	E	A	M	D	M	A*	G*	E*
T	O	S	R	R	D	M	E	P	E*	G*	M*
I	R	S	T	G	E	M	R	L	G*	P*	M*
N	S	I*	T	I	G	M	R	E	L*	P*	M*
G	T	I*	N*	N	I	M	R		M*	P*	E
A	G*	I*	N*	G	M	N	R		P*		E
N	I*	A	N*	E	N	G*	R		E		
D	N*	A	N*	X	R	G*	E*				
M	N*	A	D	A	X	G*	E*				

tape1: A O R S T • A D E G I M N R X • E •

tape2: G I N N • A E G L M P •


• Random Keys $\Rightarrow$ Run Size $\doteq 2M$

Some order $\Rightarrow$ Longer runs

(Example: $\forall$ key, less than M larger key before it $\Rightarrow$ 1 run)

• $\frac{M}{P \text{ tapes}} \Rightarrow \log_P \frac{N}{2M}$ passes.

• System architecture



• Practical consideration

- overlapping : Input, output, computing
- double buffering
- Forecasting

Practical Considerations

- Overlap Input, Output, & Computing


- Double Buffering : P-way merging

2P : input buffers
2 : output

tape 1: 1, 3, 5, 7, 8, 9, ...

tape 2: 2, 4, 6, 15, 20, 25, ...

tape 3: 1, 2, 3, 4, ...



- Forecasting $P+1$ input buffers
2 output "

Example: $3 < 4, \therefore$

5 7

• Polyphase merging

- No need to i) use 2P tapes
OR ii) Copy files between merging phases.

Example :

tape 1: AORST · IN · AGN · DEMR · GIN ·

tape 2: EGX · AMP · EL ·

tape 3:

tape 1: DEMR · GIN ·

tape 2:

tape 3: AEGORSTX · AIMNP · AEGLN ·

tape 1:

tape 2: ADEEGMORRSTX · AGIIMNPN ·

tape 3: AEGLN ·

tape 1: AADE (sorted file)

tape 2:

tape 3:

How to distribute initial runs ³¹?

T1	T2	T3	T4
0	13	11	7
7	6	4	0
3	2	0	4
1	0	2	2
0	1	1	1
1	0	0	0


$$13 = 7 + 4 + 2$$

Generalized Fibonacci #s.

Virtual Memory Environment (Easy!)

- Page demanding + Least Recently Used (LRU) page
- Locality of Reference
- Internal Sorting with few locality works well.

Example: Quick sort: 2 localities
Radix sort: 0 "




Searching

- retrieve records with **keys** matching a given key.
- dictionary, symbol tables
- **Operations**:
 - Search
 - Insert
 - delete
 - join
 - sort

• Sequential search:

- **array**: EXAMPLE $T = N$: unsuccessful
 $N/2$: successful

- **linked list**: 

- most frequently accessed records go first
- self-organized:

EXAMPLE
 ↓ Search M
MEXAMPLE
 ↓ Search L
LMEXAPE

▲ Assume locality of reference for search keys

• Binary search (sorted file)


1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
A	A	A	C	E	E	E	G	H	I	L	M	N	P	R	S	X
A	A	A	C	E	E	E	G	H	I	L	M	N	P	R	S	X
									I	L	M	N	P	R	S	X
													P	R	S	X
															S	X

$$T = \lg N$$

• Binary search Tree (dynamic)

$$T = \lg N \text{ (ave.)}$$

$$N \text{ (worst)}$$




Sort

root
↓

treeprint(x) /* in-order traversal */

```

if x ≠ nil then {
    treeprint(x↑.left);
    print Node(x);
    treeprint(x↑.right);
}
    
```



• Interpolation search

$$x = l + (r - l) \frac{v - k_1}{k_2 - k_1}$$

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
A		A	C	E	E	E	G	H	I	L	M	N	P	R	S	X
													P	R	S	X
															S	X

$$13 = 1 + 16 \cdot \frac{S - A}{X - A}$$

$$T = \lg \lg N \approx \text{constant.} \quad (\lg \lg 10^6 < 5)$$

• Deletion

delete(t, x) ↖ root of tree

repeat

$p := x;$

if $t.key < x.key$

then $x := x.l;$

else $x := x.r;$

Until $t = x;$

$C := x.r;$

if $C = \perp$ then

$x := x.l;$

elseif $C.l = \perp$ then

$C.l := x.l;$

$x := C$

else

While $C \neq \perp$ do $C := C.l;$

$x := C.l;$

$C.l := x.r;$


$x.l := t.l;$

$x.r := t.r;$



end

if $t.key < p.key$ then $p.l := x;$

else $p.r := x;$





↓ delete D





Balanced trees

- Worst case : $\log N$
- Weight balanced
- Height balanced: **AVL trees**, 2-3 trees, **2-3-4 trees**
B-trees


• **AVL-trees** (Hts difference ≤ 1)



(1)



(2)



• **2-3-4 trees**


2-node



3-node





4-node



$b \leq x < c$

Red-black tree representation (one extra bit)




- No consecutive **red** links
- Search : as binary trees

Simple
Save memory

- Insertion ?


insert + rotate
with 2
red ptrs

Insert Y ↓



Insertion:

(1) Split 4-node in searching





(2) Insert into bottom node

$$T \leq \lg N + 1$$



Example: ASEARCHINGEXAMPLE




Insert



R, C, H



I

N





G

E, X








A M P


LE



Split




Rotate



Hashing

- Scramble Keys
- Compute address in Hash table



• Hash Function:


$$h(\text{Key}) \rightarrow \{0, 1, \dots, M-1\}$$

- Similar to random number generator.

• Example: $h(\text{abc}) \rightarrow 1+2+3 \bmod M = 6$

- Collision: different keys hash to same address $x \neq y$
 $h(x) = h(y)$

• Separate chaining



• Open addressing

$$K \mapsto h_1(K), h_2(K), \dots, h_M(K)$$

$h(K)$

1) Linear probing: $h_{i+1}(K) = h_i(K) + 1 \bmod M$

2) Double Hashing $h_{i+1}(K) = h_i(K) + u \bmod M$
 $u = g(K)$

- $u \neq 0$
- $(u, M) = 1$
- $u \neq h(K)$
- $u = M-2-K \bmod (M-2)$

- $T = \text{Const}$ (average)
 N (worst)

- **Separate chaining** : (multi-lists, sequential search)

Key: A S E A R C H I N G E X A M P L E

Hash: 1 8 5 1 7 3 8 9 3 7 5 2 1 2 5 1 5 mod 11

0	1	2	3	4	5	6	7	8	9	10
	A	M	C		E		G	H	I	
	A	X	N		E		R	S		
	A				E					
	L				P					

- Linear probing $h(k), h(k)+1, h(k)+2, \dots$

Key: A S E A R C H I N G E X A M P L E

Hash: 1 0 5 1 18 3 8 9 14 7 5 5 1 13 16 12 5 mod 19

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
		A																	
S	A																		
S	A				E														
S	A	A			E														
S	A	A	C		E														R
S	A	A	C		E			H											R
S	A	A	C		E			H	I										R
S	A	A	C		E			H	I						N				R
S	A	A	C		E		G	H	I						N				R
S	A	A	C		E	E	G	H	I						N				R
S	A	A	C		E	E	G	H	I	X					N				R
S	A	A	C		E	E	G	H	I	X					N				R
S	A	A	C	A	E	E	G	H	I	X					N				R
S	A	A	C	A	E	E	G	H	I	X					N				R
S	A	A	C	A	E	E	G	H	I	X					N				R
S	A	A	C	A	E	E	G	H	I	X	E				N				R
S	A	A	C	A	E	E	G	H	I	X	E	L	M	N					R
S	A	A	C	A	E	E	G	H	I	X	E	L	M	N					R

- Clustering. How about $R(k) + C$? $(C, M) = 1$.

• Double hashing

$$h(k), h(k)+u, h(k)+2u, \dots$$

$$u = g(k)$$

Key	A	S	E	A	R	C	H	I	N	G	E	X	A	M	P	L	E
Hash 1:	1	0	5	1	18	3	8	9	14	7	5	5	1	13	16	12	5
Hash 2:	16	15	12	16	16	14	9	8	3	10	12	10	16	4	1	5	12

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	
	A																		
S	A																		
S	A				E														
S	A				E												A		
S	A				E												A	R	
S	A		C		E												A	R	
S	A		C		E			H									A	R	
S	A		C		E			H	I								A	R	
S	A		C		E			H	I					N			A	R	
S	A		C		E			G	H	I				N			A	R	
S	A		C		E			G	H	I	E			N			A	R	
S	A		C		E			G	H	I	E			N	X		A	R	
S	A		C		E			G	H	I	E	A		N	X		A	R	
S	A		C		E			G	H	I	E	A		M	N	X	A	R	
S	A		C		E			G	H	I	E	A		M	N	X	P	A	R
S	A		C		E			G	H	I	E	A	L	M	N	X	P	A	R
S	A		C		E	E		G	H	I	E	A	L	M	N	X	P	A	R

Performance

Unsuccessful Successful

$$\alpha = \frac{N}{M}$$

load factor

Separate chaining

$$1 + \frac{\alpha}{2}$$

$$\frac{\alpha + 1}{2}$$

Linear probing

$$\frac{1}{2} + \frac{1}{2(1-\alpha)^2}$$

$$\frac{1}{2} + \frac{1}{2(1-\alpha)}$$


Double Hashing

$$\frac{1}{1-\alpha}$$

$$-\frac{1}{\alpha} \ln(1-\alpha)$$

Radix Searching

Digital search tree : branch by bits, not key comparisons.



Search $M = 01101$


Insert Z
" "
 11010

$$T = \begin{cases} \lg N & (\text{average}) \\ b & (\text{worst}) \end{cases}$$

A	00001
S	10011
E	00101
R	10010
C	00011
H	01000
I	01001
N	01110
G	00111
X	11000
M	01101
P	10000
L	01100

↓ Key Strings Very Long


Radix search tree (trie) : compare Keys at leaf node only



Insert $Z = 11010$


Multiway Radix searching

- Internal ↔ External node
- 1-way branching




Patricia (Pratactical Algorithm to Retrieve Information Coded in Alphanumeric)



- index $\rightarrow$ bit examined
- upward link $\rightarrow$ external node




Insertion:



Insert $Z = 11010$



Insert $T = 10100$



External Searching

- disk is made of Pages = Continuous blocks
- Page transfer dominates searching time

• Indexed Sequential Search (ISAM)

* 1 e 2 n 3 x ← Internal memory
master index

↙ Sequential Search

Disk 1:	* 1 c 2 e	A A A C	E E E E
Disk 2:	e 1 <u>i</u> 2 <u>n</u>	E G H <u>I</u>	L L M <u>N</u>
Disk 3:	<u>n</u> 1 <u>r</u> 2 <u>x</u>	N P R <u>R</u>	S T X <u>X</u>
	page 0	page 1	page 2

$T = 2$ disk accesses.

Disadvantages : Insert B ?


B-tree

$n \leq \# \text{ records in page} \leq 2n$ (except root)

$n=2$


(1) Insert 22

• $\# \text{ records} = 2n \Rightarrow \text{split}$




(2) Delete 25, 24


• $\# \text{ records} = n$
 $\Rightarrow$ balance or merge



$\Downarrow$ Delete 25




Delete 24



B^+ -tree : Increase M_I ,

10 Internal Memory



← Keys in
Sorted order

Disk 1: 11 1 12 20 a 21 e 22 e 30 h 31 32 n 40 r 41 s 42

Disk 2: A A A C E

Disk 3: T E G H I L L M

Disk 4: N N P R R S T X X

Supports Previous(k) operations
Next(k)

Extendible Hashing

Page Capacity = 4

Insert: E, X, T, E

00101	E
00101	E
10100	T
11000	X

Disk 1: 20

Disk 2: E E T X

$R = 10010$

0:	00	01	E
	00101	E	
1:	10010	R	
	10100	T	
	11000	X	

Disk 1: 20 21

Disk 2: E E

R T X

$N = 01110$

$A = 00001$

0:	00001	A
	00101	E
	00101	E
	01110	N
1:	10010	R
	10100	T
	11000	X

Disk 1: 20 21

Disk 2: A E E N

R T X

$L = 01100$

00:	00001	A
	00101	E
	00101	E
01:	01100	L
	01110	N
10:	10010	R
11:	10100	T
	11000	X

$\begin{matrix} 00 & 01 & 10 & 11 \\ \downarrow & \downarrow & \downarrow & \downarrow \end{matrix}$
 Disk 1: 20 21 22 22

Disk 2: A E E

L N R T X

Internal Memory

10 11

bit = '0' bit = '1'

S = 10011

E = 00101

A = 00001

000:	000	01	A
	000	01	A
001:	001	01	E
	001	01	E
	001	01	E
010:	01	100	L
011:	01	110	N
100:	100	0	R
101:	100	11	S
110:	101	00	T
111:	1100		X

Disk 1: 20 21 22 22 30 30 30 30

Disk 2: A A E E E L N

Disk 3: R S T X

100 101 110 111

30 30 31 31

R S T X Z

- Insert Z = 11010 ?
- 2 disk accesses (like Indexed Sequential)
- Efficient insertion (like B-tree)
- Hash (key) → random bit string