

String Matching

- Brute-force

• Brute-force

Text $a[N]$: a b c x y z a b c d a b c d a b c x y z

Pattern $P[M]$: a b c d a b x y

Diagram illustrating the alignment of the text $a[N]$ and the pattern $P[M]$ for the brute-force matching algorithm. The text $a[N]$ is shown as a sequence of characters: a b c x y z a b c d a b c d a b c x y z. The pattern $P[M]$ is shown as a sequence of characters: a b c d a b x y. The alignment shows the pattern $P[M]$ starting at the 10th position of the text $a[N]$. The diagram includes indices i and j with arrows indicating the current positions in the text and pattern respectively, and the formula $i-j+2$ is shown above the alignment.

Brute Search

$$i := 1; \quad j := 1;$$

repeat

if $a[i] = P[j]$ then

$$i := i + 1; \quad j := j + 1;$$

else

$$i := i - j + 2; \quad j := 1;$$

until $j > M$ or $i > N$.



$i-M$

(or sentinel)



Not Found

Too bad!

• $\begin{array}{cccccccccccc|} 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & & & & & & & \end{array} \quad \begin{array}{l} 8 \cdot 5 + 5 \\ \geq \text{KMP} \end{array}$

⇒ KMP

• 1 0 0 0 0 1 0 0 0 - 0 0 0
1 0 0 0 0 0

⇒ Boyer-Moore

$$T = MN$$

Knuth-Morris-Pratt algorithm

a b c x y z a b c d a b c d a b x y z

a b c d a b x y

↑
Next[j]

KMPsearch

$i := 1; j := 1;$

repeat

if $j = 0$ or $a[i] = P[j]$ then

$i := i + 1; j := j + 1;$

else

$j := \text{next}[j];$

until $j > M$ or $i > N$;

↓
 $i - M$

↓
Not Found

i never backup

a b c x y z

a b c d a b x y

↑
j

a b c x y z

x y z

next[1] = 0

a b c x y z

a x y

next[2] = 1

a b c x y z

a b x y

next[3] = 1

a b c x y z

a b x y

a a c x y z

a a x y

next[3] = 2

• How to compute next[j] ?

x x x a b c d a b e x y z a b c d x x x x x x x

a b c d a b e x y z a b c d a b c m n p

Pattern

↑
j

↑
next[i]

↑
 $j = \text{next}[i]$

↑
i

↑
i

↑
i

↑
i

next[i]: 0 1 1 1 1 2 3 1

$\text{next}[i] = j \Rightarrow \text{next}[i+1] = j+1$
 $P[i] = P[j]$

• Init Next

$i := 1; j := 0; \text{next}[1] := 0;$

repeat

if $j = 0$ or $P[i] = P[j]$ then

$i := i + 1; j := j + 1; \text{next}[i] := j;$

else

$j := \text{next}[j]$

until $i > M$

$T = M + N$

Boyer-Moore algorithm $T = M + N$

Text : WHICH-FINALLY-HLATS-AT-THAT

Pattern: AT-THAT

AT-THAT

AT-THAT

AT-THAT

AT-THAT

$$d_1[F] = 7$$

$$d_1[-] = 4$$

$$d_2[5] = 7$$

$$d_1[-] = 4$$

BM search

$i := M; j := M;$

repeat

if $a[i] = p[j]$ then

$i := i - 1; j := j - 1;$

else if $j = M$ then

$i := i + d_1[a[i]];$

else

$i := i + d_2[j]; j := M;$

Until $j < 1$ or $i > N$

$\downarrow$
 $i+1$

$\downarrow$
Not Found

How to compute d_1, d_2 ?

i	1	2	3	4	5	6	7	8
$P[i]$	A	S	S	E	S	S	E	S
$d_2[i]$	15	14	13	7	11	10	3	

$$d_1[s] = 0$$

$$d_1[E] = 1$$

$$d_1[A] = 7$$

$$\text{others} = 8$$

$$d_1[c] = M - \max_j (P[j] = c)$$

?? ? $\downarrow$ SSSES ? ? ? ?

ASS E S S E S

A S S E S S E S

$$\therefore d_2[4] = 7$$

?? ? ? ? ? ? ? ? $\downarrow$ E ? ? ?

A S S E S S E S

Rabin-Karp algorithm

- encode string into integer.

a b d e a b c text

a b c Pattern

$d=26$

$$[abc]_{26} = 1 \cdot 26^2 + 2 \cdot 26 + 3$$

$$[abd]_{26} = 1 \cdot 26^2 + 2 \cdot 26 + 4$$

$$\begin{aligned} [bde]_{26} &= 2 \cdot 26^2 + 4 \cdot 26 + 5 \\ &= ([abd]_{26} - 1 \cdot 26^2) * 26 + 5 \end{aligned}$$

text : $a_1 a_2 \dots \underline{a_i a_{i+1} \dots a_{i+M-1}} a_{i+M} \dots a_N$

Pattern: $\underline{p_1 p_2 \dots p_M}$

$$X = [a_i \dots a_{i+M-1}]$$

$$\Rightarrow [a_{i+1} \dots a_{i+M}] = (X - a_i d^{M-1}) * d + a_{i+M} \pmod{q}$$

$$T = N + M$$

File Compression

- reduce space (encoding) $\Rightarrow$ reduce computing or communication time
- Impossible to compress every files.

• Run length

AAAA BBBB AABBBBB BCDD DQM

• alphabets only $\Rightarrow$ 4A 3B AA 5B C 3D QM

• Mixed $\Rightarrow$ Q D A B B B A A Q E B C D D D Q M
 $\uparrow \quad \uparrow 4$
 Escape character Q



• Binary file: '0', '1'

00 0000000 00000000 00000000 11111111 11111000000000	28 14 9	<u>51 bits</u> $\Rightarrow$ No EOL
(0 000000 00000000 00000000 11111111 111110000000	26 18 7	
0000 0000 00000000 00000000 11111111 11111111 10000	23 24 4	
00000000 00000000 00000000 11111111 11111111 11111000	22 26 3	
00000000 00000000 00000000 11111111 11111111 11111110	20 30 1	
00000000 00000000 00000000 11111100000000 00000000 111111	19 7 18 7	
00000000 00000000 00000000 111110000000 00000000 000000 11111	19 5 22 5	
00000000 00000000 00000000 1110000000 00000000 000000 111	19 3 26 3	
00000000 00000000 00000000 1110000000 00000000 000000 111	19 3 26 3	
00000000 00000000 00000000 1110000000 00000000 000000 111	19 3 26 3	
00000000 00000000 00000000 1110000000 00000000 000000 111	19 3 26 3	
00000000 00000000 00000000 1111000000 00000000 000000 1110	20 4 23 3 1	
0000000 00000000 00000000 1110000000 00000000 000000 111000	22 3 20 3 3	
01111111 11111111 11111111 11111111 11111111 11111111	1 50	
01111111 11111111 11111111 11111111 11111111 11111111	1 5	
01111111 11111111 11111111 11111111 11111111 11111111	1 5	
01111111 11111111 11111111 11111111 11111111 11111111	1 50	
01111111 11111111 11111111 11111111 11111111 11111111	1 50	
01100000 00000000 00000000 00000000 00000000 000000 0011	1 2 46 2	


Huffman Coding

- encode frequent character with shorter string


~~11~~ 3 3 1 2 5 1 2 6 2 4 5 3 1 2 4 3 2
A B C D E F G I L M N O P R S T U



count[30] = 21
dad[18] = -30
dad[34] = 30



- With priority queue



I
 $\text{Code}[9] = 1 = '001'$
 $\text{len}[9] = 3$

$\Leftrightarrow$ external nodes of a binary tree

- **prefix code**: no sequence is a prefix of another
- **Optimum prefix code**: Shortest encoded string

Example of non-prefix code

A: 10

B: 011


C: 01110

01110 = BA ?
 C ?

- Dynamic Huffman Coding

Cryptology (密碼學)

- Cryptograph : encode, encryption, (編碼), encipher
- Cryptoanalysis : decode, decryption, (解碼), decipher
- Applications : military, file system, electronic fund transfer
- Cryptosystem :



Simple methods

- Caesar Cipher ($K=3$)

$$F: N^{th} \rightarrow (N+K)^{th}$$

Plaintext: ATTACK AT DAWN

$K=1$

Ciphertext: BUUBDLABUAEBXO

- Even $F: 1-1 : \{A, \dots, Z\} \rightarrow \{A, \dots, Z\}$
is easy to break by frequency counting.

- Vigenere cipher

Key : A B C A B C A B C

Plaintext : A T T A C K A T

Ciphertext : B V W B E N A C W


- Vernam Cipher (one time pad)

- $\forall A \in \text{Key} \hookrightarrow F_A, 1-1, \text{onto} : \{A, \dots, Z\} \rightarrow \{A, \dots, Z\}$
- Key as long as plaintext
- The Only Secure system

- Binary file

$$\text{Ciphertext} = \text{Key} \oplus \text{plaintext}$$

- Encryption/Decryption Machine (Hardware)



Number Theory

Theorem : $(a, p) = 1 \Rightarrow a^{p-1} \equiv 1 \pmod{p}$
(Fermat) p : prime

Pf: (i) $\{1 \cdot a \bmod p, 2a \bmod p, \dots, (p-1)a \bmod p\}$
 $= \{1, 2, \dots, p-1\}$

Example: $\{3 \bmod 5, 6 \bmod 5, 9 \bmod 5, 12 \bmod 5\}$
 $= \{3, 1, 4, 2\}$

$$\begin{aligned} \therefore xa \equiv ya \pmod{p} &\Leftrightarrow p \mid (x-y)a \\ &\Leftrightarrow p \mid x-y \\ &\Leftrightarrow x \equiv y \pmod{p} \end{aligned}$$

$$(ii) (p-1)! a^{p-1} \equiv (p-1)! \pmod{p}$$
$$\Rightarrow a^{p-1} \equiv 1 \pmod{p}$$

Example: $3^{5-1} \equiv 1 \pmod{5}$
 $4^{7-1} \equiv 1 \pmod{7}$ ($\because 4^3 = 64 \equiv 1 \pmod{7}$)

Theorem $(M, p) = (M, q) = 1 \Rightarrow M^{(p-1)(q-1)} \equiv 1 \pmod{N}$

Pf: $M^{p-1} \equiv 1 \pmod{p} \Rightarrow M^{(p-1)(q-1)} \equiv 1 \pmod{p}$
 $M^{q-1} \equiv 1 \pmod{q} \Rightarrow M^{(p-1)(q-1)} \equiv 1 \pmod{q}$
 $\Rightarrow M^{(p-1)(q-1)} \equiv 1 \pmod{pq}$

Theorem (Euler) $(a, N) = 1 \Rightarrow a^{\phi(N)} \equiv 1 \pmod{N}$

$$\varphi(N) := \# \text{ relative primes in } \{0, 1, 2, \dots, N-1\}$$

• Public-Key systems

E : public key

D : private key

(1) $D(E(M)) = M$, $\forall$ message M . $\Rightarrow E: 1-1$.

(2) All (D, E) distinct

(3) $E \not\Rightarrow D$ (Even, $M, E(M), \not\Rightarrow D$)
 $M, E(M)$

(4) E, D are easy to compute.

• Proposed by Diffie, Helleman, 1976.

• Rivest - Shamir - Adleman (**RSA**) algorithm, 1978.

P, q prime

$$N = P \cdot q$$
$$\varphi(N) = (P-1)(q-1)$$


By primality test

$N \not\Rightarrow P, q$ Factorization is Hard

$$(d, \varphi(N)) = 1 \Rightarrow ed + k\varphi(N) = 1 \quad (d: \text{prime})$$

E = (N, e) public Key

D = (N, d) private Key



$$\therefore \underbrace{Me}_{\text{cipher}}^d = M^{-k\varphi(N)+1}$$
$$= M^{-k(P-1)(q-1)+1}$$
$$\equiv M \pmod{N}$$

Example: $P=3, q=7$

$$N = 21$$

$$\phi(N) = 12$$

$$d=5, e=5 \quad \because 5 \cdot 5 - 2 \cdot 12 = 1$$

$$M=3 \quad M^e \bmod N = 3^5 \bmod 21 = 12 \leftarrow \text{Cipher}$$

$$12^d \bmod N = 12^5 \bmod 21 = 3$$

$$12 = 2 \cdot 5 + 2$$

$$5 = 2 \cdot 2 + 1$$

$$\Rightarrow 1 = 5 - 2 \cdot (12 - 2 \cdot 5) \\ = 5 \cdot 5 - 2 \cdot 12$$

Why RSA algorithm works? $(N, e, M^e \xrightarrow{?} M) \bmod N$
 $\xrightarrow{?} d$

$$N \xrightarrow{?} P, q \Rightarrow \phi(N), d \Rightarrow M$$

$\therefore$ The only way to factorize N is to test primes
 $2, 3, 5, 7, \dots, \sqrt{N}.$

$$O(e^{\sqrt{\ln N \ln \ln N}})$$

N # digits	# operations Factorize N	Computing time with Cray
50	1.4×10^{10}	4 Hours
80	1.3×10^{13}	150 Days
100	2.3×10^{17}	74 Years
200	1.2×10^{23}	3.8×10^9 Years

• Digital Signature

(an application of public key systems)

$$(E_i, D_i) \xrightarrow{M'} (E_j, D_j)$$

$$E_i(D_j(E_j(D_i(M)))) = M$$

$\uparrow$
 $M' = \text{message } i \text{ sends to } j$

Require: (1) $D(E(M)) = E(D(M)) = M.$

(2) i can't deny, j can't forge $D_i(M) !!$

• Knapsack problem

- Given $\{a_1, a_2, \dots, a_n\}$, K , $\exists a_{i_1} + a_{i_2} + \dots + a_{i_p} = K$?
 $\Leftrightarrow a_1 x_1 + a_2 x_2 + \dots + a_n x_n = K, x_i = 0, 1$?
- General $\{a_n\}$: NP-complete, **No** polynomial time algorithm.
- Super-increasing $\{a_1, a_2, \dots, a_n\}$; $\forall j=2, \dots, n, a_1 + \dots + a_{j-1} < a_j$
can be solved in $O(N)$ time.

Example: (3, 5, 9, 20, 44)

$$3x_1 + 5x_2 + 9x_3 + 20x_4 + 44x_5 = 69 \pmod{89}$$

$$\begin{aligned} &= 25 & x_5 &= 1 \\ &= 5 & x_4 &= 1 \\ & & x_3 &= 0, x_2 = 1 \\ & & x_1 &= 0 \end{aligned}$$

$$4 * 67 \equiv 1 \pmod{89}$$

$$\Rightarrow *4 \uparrow \downarrow *67$$

$$3x_1 + 5x_2 + 9x_3 + 20x_4 + 44x_5 \equiv 69 \pmod{89}$$

$$23x_1 + 68x_2 + 69x_3 + 5x_4 + 11x_5 \equiv 84 \pmod{89}$$

• Knapsack cipher system (Hellman & Merkle, 1978)

public key : (23, 68, 69, 5, 11), 89

private key: (3, 5, 9, 20, 44), 4

plaintext : $M = (01011)_2$

ciphertext : $M' = 84$

Receiver (i) $4 * 84 \equiv 69 \pmod{89}$
(ii) Solve x_i , obtain $(01011)_2$

• But Shamir (1983) showed, this method is breakable!

Computational Geometry

- **Objects:** point : (x, y)
line, segment, array : (P, q)
polygon : $P_0, P_1, \dots, P_N, P_0$
planar subdivision
- **Questions:** intersection Static / dynamic
point - location
decomposition
- **Applications:**
 - Graphics,
 - CAD
 - VLSI
 - Image Processing
 - Pattern Recognition
 - Robotics
- **Paradigms:** Incremental Construction
Plane sweep
Locus
Divide & Conquer
Geometric Transformation
Prune & Search
Dynamization

Scan-conversion

- Geometric objects $\rightarrow$ Pixels, Bitmaps
(line, area)

- Draw(P, Q)


dot(P);

dot(Q);

if $|x_1 - x_2| > 1$ or $|y_1 - y_2| > 1$ then

draw($P, \frac{1}{2}(P+Q)$);

draw($\frac{1}{2}(P+Q), Q$);



- Incremental algorithm

$$m = \frac{y_2 - y_1}{x_2 - x_1}; \quad b = y_1 - mx_1$$

$$y - y_1 = m(x - x_1)$$

$$y = mx + y_1 - mx_1 \\ = mx + b$$

$$x \rightarrow x+1 \\ y \rightarrow y+m$$

Program:

$y := y_1;$

for $x := x_1$ to x_2 do

dot($x, \text{round}(y)$);


$y := y + m;$

Line Intersection

$$r e^{i\theta} = \frac{a+ib}{x+iy} = \frac{(x-iy)(a+ib)}{x^2+y^2}$$


$$\therefore r \sin \theta = bx - ay > 0$$

$$\iff 0 < \theta < 180^\circ$$



Counter Clock Wise


$$CCW(O, X, A) = +1$$




$$-1$$




$$-1$$



$$0$$



$$+1$$



$$bx - ay > 0$$

$$bx - ay < 0$$

$$bx - ay = 0 \left\{ \begin{array}{l} ax < 0 \text{ or } by < 0 \end{array} \right.$$

$$x^2 + y^2 \geq a^2 + b^2$$


else

Segments


$$L_1 = (O, X)$$

$$L_2 = (A, B)$$


$$L_1 \cap L_2 \neq \emptyset \iff CCW(O, X, A) * CCW(O, X, B) \leq 0 \text{ AND } CCW(A, B, O) * CCW(A, B, X) \leq 0$$




$$CCW(O, X, A) = 0$$



$$CCW(O, X, A) = -1$$



Simple closed path : thru every points, does not intersect itself



Method: order points according to θ to an anchor point.

• How to find $\theta = \tan^{-1} \frac{y}{x}$?

$$\theta = \tan^{-1} \frac{y}{x} \quad \uparrow \quad \text{in (I) 象限.}$$

$$\Leftrightarrow \frac{y}{x} \quad \uparrow \quad "$$

$$\Leftrightarrow 0 \leq \frac{y}{x+y} \leq 1 \quad \uparrow \quad "$$

$$\frac{b}{a} < \frac{d}{c} \Leftrightarrow \frac{b}{a+b} < \frac{d}{c+d}$$

i.e., $-1 \leq \frac{y}{|x|+|y|} \leq 1 \quad \begin{matrix} \uparrow & \text{I, IV} \\ \downarrow & \text{II, III} \end{matrix}$

Program

$$t := \frac{y}{|x|+|y|}; \quad (0, x=y=0)$$

if $x < 0$ then (II, III)



$$t := 2 - t;$$

elseif $y < 0$ then (IV)

$$t := 4 + t;$$


$$0 \leq t \leq 4$$

$$0 \leq 90t \leq 360$$




Inclusion in Polygon $p_0, p_1, \dots, p_N = p_0$

P in Polygon?



in $\iff$ odd intersection
out $\iff$ even



- Go from one side to another $\Rightarrow$ count +1

Program $j := 0; \text{count} := 0;$


for $i := 1$ to N do

if $P_i \in L$ then {

if $\overline{P_j P_i} \cap L \neq \emptyset$ then
 count := count + 1;

$$j = i;$$

}



- Choose P_1 : min x among min y coordinates

$$p_i \in L \Rightarrow p_0 \notin L$$

$$\quad \quad \quad \parallel$$

$$\quad \quad \quad p_N$$

Bug: $p_0 \in L, p_1 \notin L$.

Convex Hull


(curve)

Smallest convex polygon contains all points

Goal: find vertices define the Hull.

Properties of CH:

- all points on same side of edge in CH.
- points with $\begin{Bmatrix} \max \\ \min \end{Bmatrix} \begin{Bmatrix} x \\ y \end{Bmatrix}$ are vertices of CH.



Package Wrapping (Jarvis Marching)

p_0 : smallest y


p_1 : $\min \theta$

p_2 : $\min \theta$, among $> v$

$\vdots$

until $p_n = p_0$

$$T = NM$$




Graham Scan

- Choose 1 point, sorting according to θ
- Add 1 pt, modify to keep CH property: i.e., all points on same side of Hull edge. (No right-turn)

Example:

- Add K
- B, K different sides of $\overleftrightarrow{PN}$
- B, K same side of $\overleftrightarrow{NL}$
 $CCW(N, L, K) < 0$

$$T = N \log N + O(N)$$




BMJLNPKFIECOAHGD

Interior Elimination

- Pick 4 points on the Hull, discard every point inside, then
- Use Graham scan.

4 points can be

- (1) max, min, x
max, min, y
- (2) max, min, $x+y$
max, min, $x-y$



Complexity

- Package Wrapping : NM
- Graham Scan : $N \log N$ (optimum)
- Interior Elimination : $N \log N$ (worst)
 N (in practice)


- Complexity of Convex Hull = Complexity of sorting = $N \log N$

proof (i) Sorting $\propto$ Computing Convex Hull


To sort $\{a_i\}$: (1) $S = \{e^{ia_i}\}$ or $\{(a_i, f(a_i))\}$, $f(x) = x^2$ (or e^x)
(2) $CH(S)$

$$\therefore \text{Convex Hull} \geq N \log N$$

(ii) $\exists N \log N$ CH algorithm



OR



CH

Sorting

$N \log N$

$N \log N$

Range Searching (Multi-key searching)

- Find Record = $(x_1, \dots, x_N)$, s.t., $x_1 \in [a_1, b_1]$
 $x_2 \in [a_2, b_2]$
 $\vdots$
 $x_N \in [a_N, b_N]$
↑
attribute

$N=1$

- $a_1 = b_1$: internal searching
- Preprocessing
Range-search
- Method 1

Preprocessing : sorting

$N \log N$

Range-search : binary search

$R + \log N$

Keys: 1, 2, 3, 4, 5, 6, 7, 8, 9
 $Q = [2.5, 7]$ ↑ ↑

Method 2


Preprocessing : binary search tree

$N \log N$

Range-search: Search($l, [a, b]$)

$R + \log N$

if $a \leq l.\text{key}$ then search($l.\text{left}, [a, b]$);
if $l.\text{key} \leq b$ then search($l.\text{right}, [a, b]$);
if $a \leq l.\text{key} \leq b$ then print($l.\text{key}$);



$Q = [2.5, 7]$

$$N=2$$

$$Q = [a_1, b_1] \times [a_2, b_2]$$

• Sequential search

$\forall 1 \leq i \leq N$, check $(x_i, y_i) \in Q$

• Projection


(1) $\forall i$, check $x_i \in [a_1, b_1]$?

(2) check $y_i \in [a_2, b_2]$? among those i pass (1)

• Grid method (Atlas)



Grid $[0..4, 0..4]$

Grid $[0, 1] \rightarrow G, Z$





• K-D tree


• Quad-tree



2-D tree




Geometric Intersection : Sweeping = Binary tree + range searching





• Binary tree $\supset \{ \text{non-empty} \neq \emptyset \}$
Key is x coord.

B B D E F H J C G
D I C A G F J E I




range search H



$$T = N \log N + I$$

Search A

General Segment Intersection



x -structure

a, b
c, a, b
a, c, b
a, b, c
b, a, c
b, a
a

(priority queue)

y -structure

8, 9
7, 8, 9
6, 7, 8, 9
5, 6, 7, 8, 9
4, 6, 7, 8, 9
3, 4, 7, 8, 9
2, 3, 7, 8, 9
1, 2, 3, 7, 8, 9 ↑

Property: Intersecting lines must be adjacent in x -structure some time

Algorithm

While y -structure $\neq \emptyset$ do {

delete p from y -structure;

$P = \text{Low}(L) \Rightarrow$

(1) Insert (L, x) ;

(2) $\begin{array}{c} \text{---} \text{---} \text{---} \\ L_l \quad L \quad L_r \end{array}$ Insert $(L \cap L_l, y)$ if exist.
Insert $(L \cap L_r, y)$

$P = L_1 \cap L_2 \Rightarrow$

(1) Interchange L_1, L_2 in x -structure

(2) $\begin{array}{c} L_l \quad \quad L_r \\ \text{---} \text{---} \text{---} \\ L_2 \quad L_1 \end{array}$ Insert $(L_l \cap L_2, y)$ if above
Insert $(L_1 \cap L_r, y)$ sweep L

$P = \text{High}(L) \Rightarrow$


(1) Delete (L, x) ;

$\begin{array}{c} \text{---} \text{---} \text{---} \\ L_l \quad L \quad L_r \end{array}$ Insert $(L_l \cap L_r, y)$ "

}

$$T = N \log N + I \log N$$

Closest Points



Algorithm (divide & conquer)

(1) Find closest pairs δ_1 of L and δ_2 of R recursively

(2) $\delta = \min(\delta_1, \delta_2)$

(3) Project $P_1 \rightarrow P_1^*$ and $P_2 \rightarrow P_2^*$ sorted by y-coord.

(4) $\forall P \in P_1^*$, scan ≤ 6 pts in P_2^* (within δ)


Get δ_e

(5) $\delta_s = \min(\delta, \delta_e)$

Presort y coordinate

$$\Rightarrow T(N) = 2T\left(\frac{N}{2}\right) + O(N)$$


$$= O(N \log N)$$



Voronoi Diagram

Given $a_1, \dots, a_N$


- Voronoi polygon (a) := all points closer to a than other a_i 's.
vertices $\leq 2N-4$
edges $\leq 3N-6$
- Voronoi diagram := $\bigcup_a \text{polygon}(a)$
- Voronoi Dual
(Delaunay triangulation)
triangulation of all points
- degree(vertex) = 3 (outside)
- Convex Hull $\subset$ Dual
- Polygon(a) unbounded
 $\Leftrightarrow a \in \text{convex Hull}$



Applications


- closest pair : find closest pair of a_i 's ($\subset$ Dual)
- all nearest neighbor : find nearest neighbor of a_i ($\subset$ Dual)
- nearest neighbor : find nearest a_i of a point P ($P \in \text{poly}(a_i)$) ($\subset$ Dual)
- computing convex Hull : ($\subset$ Dual)
- Euclidean Minimum Spanning Tree : ($\subset$ Dual)
find a tree connects all a_i 's with minimum distance.
- Can compute Voronoi Diagram in $O(N \log N)$
 $\Rightarrow$ All can be solved in $O(N \log N)$

Compute Voronoi Diagram in $O(N \log N)$ time
(Divide & Conquer)




Compute Voronoi Diagram in $O(N \log N)$ time

(Divide & Conquer)



$$VD = (VD(L) \cap L(\sigma)) \cup \sigma \cup (VD(R) \cap R(\sigma))$$




• Compute Supporting Lines $T = O(N)$

(1) Compute $CH(L)$; $CH(R)$

(2) Find interior point P of $CH(L)$, (3 点 ≠ 内部)

(3) P interior point of $CH(R)$?



(4) Merge ^{vertices of} $CH(L)$; $CH(R) / CH(R^*)$

(5) Graham Scan



Property: P : interior point of CH

$\Leftrightarrow$ Angles of vertices of $CH \nearrow$

• Algorithm for convex hull

$$\begin{aligned} T(N) &= 2T\left(\frac{N}{2}\right) + O(N) \\ &= O(N \log N) \end{aligned}$$